

BORN YODHA

A winning combination of performance, ruggedness and style that not only aids your business but leads it too.

STRONG AGGREGATES



ENGINE The newly redesigned TATA 4 SPCR TCIC 4-CYLINDER 3.0 L engine with a capacity of 2956 cc is powered to perform.



POWER 86 HP power with 250 Nm Torque.



SPEED Unrivalled Speed.



LARGEST LOAD BODY Rated payload of 1250 kgs.



HIGHEST GROUND CLEARANCE With ground clearance of 210mm, it's the highest in the category.



TYRES The wide 16" (215/75 R) radial tyres of the Yodha ensure better safety.



Front: 6 Semi-Elliptical Leaf Springs + Anti-Roll bar Rear: Innovative Two-stage Semi-Elliptical Leaf Springs - 9 Leaves.

SOPHISTICATED COMFORT



FLAT BENCH SEAT Accommodates 3 people comfortably, unlike any in the category.



LOCKABLE GLOVE BOX Keep your important documents safe.



TRIP METER WITH DUAL READING A unique feature that is ideal for Fleet Owners to keep track of the vehicle movement & routes taken during the journey.



INTENSITY CONTROL CABIN LIGHT Allows the driver to adjust the intensity of the cabin light, depending upon the surroundings outside.



ADJUSTABLE ANTI-GLARE REAR VIEW MIRROR The rear view mirror of the Yodha can be adjusted by the driver to reduce the glare from outside.



WORLD-CLASS CABIN SPACE Newly designed spaces for maximum comfort.

FLUID PERFORMANCE



GREAT RESTART GRADEABILITY OF 22% Keep climbing them even after sudden stops on steep roads.

FASTER PICK-UP Enables faster trips.

EFFECTIVE BRAKING Ensures complete safety while driving.

BEST CARE

- BEST-IN-CLASS WARRANTY Comes with the best-in-class warranty of 3 years or 3 lakh km*.
- BEST-IN-CLASS SERVICE INTERVALS The 15,000 km oil change interval so you stay on-road longer while saving 1 EMI every year.
- 21 POINT LIFE TIME LUBRICATED POINTS Yodha has 21 Life Time Lubricated Points which means reduced maintenance cost and faster service.



FEATURES YODHA BS IV

Type Tata 4SPCR TCIC 4-cylinder BS IV

Capacity 2956 cc

 Max. Output
 64 kW (85 HP) @ 3000 rpm

 Max. Torque
 250 Nm@ 1000-2000 rpm

Fuel Tank Capacity 45 L

CLUTCH & TRANSMISSION -------

Clutch Single plate dry friction type 260 mm Dia

Gearbox GBS 76 – 5/4.1

Synchromesh 5 forward + 1 reverse

Steering Power steering

SUSPENSION

Front 6 Semi-Elliptical Leaf Springs

Rear Innovative two-stage Semi-Elliptical Leaf

Springs - 9 Leaves

Anti-roll bar Front

BRAKES ------

Front Hydraulic, twin-pot Disc Brakes

Drum Brakes

Tyre 215/75 R 16" Radial

Rim size 16-Inch

OVERALL VEHICLE DIMENSIONS (mm)

Width 1860 Length 5350 Height 1810 Ground Clearance 210 Wheel Base 3150

Internal Load Body (L x B) 2550 (8.4 ft) x 1750 (5.7 ft)

Turning Circle Radius 6250

WEIGHT (kg)

 GVW
 3100

 Kerb Weight
 1850

 Payload
 1250

PERFORMANCE

Gradeability 30% Restart Gradeability 22%

Top Speed

Seating type Lay Flat Seat

WARRANTY TERMS

Warranty (on Driveline) 3 years or 3 Lakh km (whichever is earlier)

For more information contact:

Rear

WHEELS & TYRES

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

As per terms & conditions in the operator's service manual.







